

# WI-FI ATTACHMENT

## FOR AGM THERMAL IMAGING SYSTEMS

External WiFi Module for AGM thermal imaging systems will help you to connect your device and transmit the entire image captured by your thermal vision device to your smartphone or tablet. After a few simple steps your mobile device could become a viewfinder. Photo and video recorded by thermal vision system will be initialized via smartphone and it will not even distract you from observation session.

Wi-Fi Attachment works with Asp 336/640, Cobra 336/640, Python 336/640, Anaconda 336/640, Protector, Explorator, Secutor, Victrix.

<b>Transmitting Frequency</b>	2400...2483.5 MHz
<b>Video Resolution</b>	VGA 640*480, 30 fps
<b>Video Compression</b>	H.264
<b>Transmission Distance</b>	up to 30 m
<b>Interface</b>	micro USB
<b>Battery type</b>	Li-Ion, 970 mAh, 3.7V
<b>Operation Time</b>	up 4 hours
<b>Operation Temperature</b>	- 20 to +50 °C / - 4 to +122 °F
<b>Weight</b>	74 g / 2.6 oz
<b>Dimensions</b>	58 x 44 x 37 mm / 2.3 x 1.7 x 1.4 in
<b>Included Accessories</b>	Video Cable, RCA Cable



MAIN OFFICE  
 173 West Main Street | PO Box 962 | Springerville | AZ 85938 | USA  
 Tel. +1.928.333.4300 | info@agmglobalvision.com  
 www.agmglobalvision.com

EUROPEAN OFFICE  
 #6 Andrey Lyapchev Blvd | Sofia | P.C. 1756 | Bulgaria  
 Tel. +35.988.412.5573 | info@agmglobalvision.eu  
 www.agmglobalvision.eu