

## PVS-7

## NIGHT VISION GOGGLES

The PVS-7 is widely recognized for its unsurpassed dependability and ergonomic design. This U.S. Military-grade night vision goggle system has repeatedly proven its worth in combat, and is the highest-quality AN/PVS-7 B/D system on the market. The PVS-7 can be outfitted with high-performance Gen 2+ and Gen 3 image intensifier tubes (available in Green phosphor or P45 white phosphor).

The PVS-7 is equipped with Automatic Brightness Control (ABC) to adjust image brightness in changing light conditions to maintain image definition and clarity. The built-in infrared illuminator provides a light source beyond the visible spectrum to enable the user to operate in complete darkness without being detected.

Additionally, the PVS-7 has a bright light cutoff feature to protect the image tube from sources of intense light, and a flip-up shutoff feature that can be used with the optional helmet mount system. The PVS-7 has two LED indicators in the eyepiece for the IR illuminator on and low battery indicator.

Lightweight, tough, and versatile, the PVS-7 can be handheld, or mounted to the user's head/helmet. It is compatible with afocal magnifier lenses for superior long-range viewing.



- Compact, rugged design
- Waterproof
- Head or helmet-mountable for hands-free operation
- Ergonomic, simple, easy-to-operate controls
- Built-in Infrared illuminator
- 3-year warranty







Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.

## **SPECIFICATIONS**

Image Intensifier Tube	Gen 2+ or Gen 3
Magnification	1x
Lens System	27 mm; F/ 1.2
FOV	40°
Focus Range	0.2 m to infinity
Diopter Adjustment	-6 to +2 diopters
LED Indicators (in the FOV)	- Low Battery - IR On
Automatic Brightness Control	Yes
Bright Light Cut-Off	Yes
Infrared Illuminator	Yes
Battery Type	2 AA Alkaline or 1 Lithium (BA-5567/ U)
Battery Life (Operating)	Up to 60 hours at 20°C
Operating Temperature Range	-40°C to +50°C (-40°F to +122°F)
Storage Temperature Range	-50°C to +70°C (-58°F to +158°F)
Waight	0.60 kg (1.5 lb)
Weight	0.68 kg (1.5 lb)
Overall Dimensions	162 × 152 × 76 mm (6.4 × 6.0 × 3.0 in)

Specifications are subject to change without notice. Images are for illustration purposes only.

## **OPTIONAL EQUIPMENT**

	50 Long-Range Infrared Illuminator comes included geable Battery and Charger UX850IR1)
AGM Afocal	Magnifier Lens Assembly, 3X
(P/N 61023X	(A1)
AGM Afocal	Magnifier Lens Assembly, 5X
(P/N 61025X	(A1)
<b>AGM 7.4x Le</b>	ens for PVS-7
(P/N 61018X	L1)
MICH Helme	et Mount Assembly
(P/N 6103MF	HM1)
PASGT Helm	net Mount Assembly
(P/N 6103PF	HM1)
Hard Case (P/N 6610HC	CS1)



MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

 $\label{thm:condition} \mbox{EUROPEAN OFFICE} \ | \ \# 6 \ \mbox{Andrey Lyapchev Blvd} \ | \ \mbox{Sofia, P.C. } 1756 \ | \ \mbox{Bulgaria} \ \mbox{Tel.} + 35.988.560.0326 \ | \ \mbox{info@agmglobalvision.eu} \ | \ \mbox{www.agmglobalvision.eu} \$