

ObservIR LRF 25-256

THERMAL AND DIGITAL BINOCULARS



The AGM ObservIR LRF Thermal & Digital Day/Night Vision binoculars are some of the most technologically advanced and feature-packed optics in the world. The primary engine behind these binoculars lies within the main thermal viewing channel, with its high-sensitivity 12-micron detector. Unlike other thermal binoculars on the market, the ObservIR LRF also come outfitted with a digital day/night channel as well, which is great for aiding in recognition of targets detected by the thermal channel. The built-in 1,000m laser rangefinder simply takes the ObservIR LRF to another level, and this is without even mentioning its 64GB of internal memory and Wi-Fi compatibility.

Providing an unrivaled image quality in compact housing, the ObservIR LRF 25-256 features a 25mm thermal lens and a 256x192 thermal sensor with a high refresh rate of 50Hz. The ObservIR LRF binoculars also come packed with numerous software improvements, and many features that have become commonplace in AGM products: high-sensitivity thermal detector, 3840x2160 ultra-low light CMOS sensor, various viewing modes, multiple color palettes, picture-in-picture mode, built-in laser rangefinder, GPS module, long-range IR illuminator, up to 8 hours of battery life on removable, rechargeable battery pack, USB Type-C port for external power capabilities, IP67 waterproof rating. The package includes two battery packs, wrist strap, tripod adapter and charger.

- Dual-spectrum thermal and digital day/night system
- 12 μ m high-sensitivity thermal sensor
- 256x192 thermal resolution
- 1x, 2x, 4x digital zoom
- Digital image processing technology
- Ultra-low illumination optical channel
- 3840x2160 optical resolution
- Built-in IR illuminator
- Eye-safe 1,000 m laser rangefinder
- 1920x1080 resolution, 0.49-inch OLED display
- Digital Magnetic Compass
- Built-in GPS module
- Video/audio recording and snapshot capture
- Built-in 64 GB EMMC storage
- Wi-Fi hotspot
- Standby mode
- 8 hours of continuous operation on a single charge
- Auto screen-off function to saving energy
- External power supply capability
- Waterproof and dustproof
- 5-year warranty



Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.

SPECIFICATIONS

Thermal Channel Image Sensor	12µm Uncooled Focal Plane Array
Thermal Channel Resolution	256 × 192
Thermal Channel Refresh Rate	50 Hz
NETD	Less than 35 mK (25°C, F#=1.0)
Thermal Channel Lens System	25 mm; F1.0
Thermal Channel Magnification	4.5x, 9x, 18x
Thermal Channel Field of View	7.0° × 5.3°
Thermal Channel Detection Range (6' object)	1,200 m
Thermal Channel Palettes	Black Hot, White Hot, Red Hot, Fusion
Thermal Scene Modes	General, Compressed
FFC (Flat Field Correction)	Auto, Manual, External Correction
Hot Tracking (Thermal Channel)	Yes
Optical Channel Image Sensor	3840×2160, 1/1.8" Progressive Scan CMOS
Optical Channel Magnification	5.5x, 11x, 16.5x, 22x
Optical Channel Field of View	6.9°× 4.1°
Optical Channel Lens System	60 mm, F2.2
Optical Channel Modes	Day, Night, Auto
Optical Channel Viewing Range at Night	400 m
Diopter Adjustment	-5D to +3D
Interpupillary Adjustment Range	60 mm to 74 mm
Display	1920×1080, 0.49 inch, OLED, 50 FPS
Distance Measurement	Laser Rangefinder: up to 1,000 m, ±1 m accuracy
Laser Wavelength	905 nm
Laser Safety Class	Class 1
Infrared Light	Built-in 850nm Smart IR. Power and beam angle adjustment
Wi-Fi Hotspot	Yes
PIP	Yes
Digital Magnetic Compass	Yes
GPS	Yes
Zoom Pro	Yes
Image Boost 2.0	Yes
Standby Mode	Yes
Storage	Built-in EMMC (64 GB)
Video/Audio Recording	Yes / Yes
Image Capture	Yes
Local Album	Yes
Battery Type	Two replaceable and Rechargeable Li-ion 18650 Battery
Battery Life (operating)	8 hours continuous running (@25°C, WiFi, IR and LRF off)
Power	5V DC, 2 A; USB Type-C interface; Support External Power Supply; Support Direct Charging
Operating Temperature	-30°C to 55°C (-22°F to 131°F)
Protection Level	IP67 (Waterproof)
Dimensions	221×142×71 mm (8.7×5.6×2.8 in)
Weight (w/o batteries)	0.89 kg (1.96 lb)

Specifications are subject to change without notice.
Images are for illustration purposes only.



MAIN OFFICE | 2407 E Interstate 30, Suite 100, Grand Prairie | TX 75050, USA
Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | #6 Andrey Lyapchev Blvd | Sofia, P.C. 1756 | Bulgaria
Tel. +35.988.560.0326 | info@agmglobalvision.eu | www.agmglobalvision.eu

www.agmglobalvision.com